

Customer's address (Rubber Stamp - black)

Inquiry/Order Form for EV and KV Valves

Order-No: _____ Date: _____

Ordered by: _____ Telephone: _____

Blain Hydraulics GmbH
 Pfaffenstr. 1
 74078 Heilbronn / Germany
 Tel.: 07131/28210
Fax.: 07131/282199
E-Mail: info@blain.de

VALVE SPECIFICATIONS	Pos. 1	Pos. 2	Pos. 3	Pos. 4	Pos. 5	Pos. 6	Pos. 7	Pos. 8	Example
Client.No.									
Delivery Required (Week)									42
Quantity									2
1) Port Size (EV) 2) Typ (EV/KV) 3) Flow Guide									¾" 100/05
4) Solenoid Voltage AC or DC									110 DC
5) Pump (lpm / gpm)									100
6) Empty Car Pressure (bar / psi - static)									30
Loaded Car Pressure (bar / psi - static)									46
Piston Diameter (mm / inch)									1x70
Car Speed up/down (m/s - feet/min - only EV)									0.6 / 0.8

OPTIONS		EV	KV								
Pressure Compensated Bypass	CU	●									X
Pressure Compensated Down	CX	●									
Hand Pump built-on	HP	●	●								X
Emergency Lowering, 12/24 V	EN	●	●								12 V DC
Slack Rope Valve	KS	●	●								X
Extra Down Valve Manual	HX	●									
Extra Down Solenoid	MX	●									
Manual Lowering for MX	HM	●									
Slack Rope Valve HX or MX	KS	●									
CSA Coils	CSA	●	●								
Coils with Diode Lamps	LM	●	●								
Ball Valve (select size)	BV	●	●								BG 1 ½"
Pressure Switch 10 - 100 bar	DH	●	●								
Pressure Swich 1 - 10 bar	DL	●	●								X

1) 2) 3) 4) or 1) 2) 4) 5) 6) have to be specified. Further details allow us to optimise the preadjustment of the valves.